




## SMART CONNECT KNX Hue

Product	Order number	VE	PP
 SMART CONNECT KNX Hue DRA, TP1	1-0002-003	1	1

### Technical data

Rated voltage:	DC 24 V to 30 V
Power consumption:	2 W (24 V DC external supply)
Ambient temperature:	0 °C to +45 °C
KNX communication:	KNX/TP, S-Mode
KNX medium:	TP1-256
IP communication:	Ethernet 10/100 BaseT
Connections:	2x RJ45 (integrated switch) Connection and branching terminals for KNX and 24 V
Dimensions:	2 HP (DRA plus)

### Information

Operate the Philips Hue lighting system via KNX. Colour value, temperature and brightness can be defined for every light, making each completely customisable.

#### Features:

- Separate control of up to 25 Philips Hue lights
- Support of up to five Philips Hue Bridges per device
- Switching and dimming
- Individual control of RGB colour values
- Individual control of the colour temperature
- Configuration of switch-on brightness per lamp via ETS or device website
- Configuration of dimming behaviour per lamp via ETS or device website
- Calling up Philips Hue scenes
- Signal flashing of Philips Hue scenes (specific duration, return to original state)
- Alert flash per lamp
- Colour gradient function per lamp
- Connection status of Bridge or lamps on KNX
- ETS product database entry with channel structure
- Simple integration into KNX
- Extensions via firmware updates

Philips and Hue are registered trade marks of Koninklijke Philips Electronics NV.

The product may slightly differ from the illustration.

**ise Individuelle Software  
und Elektronik GmbH**  
Osterstraße 15  
26122 Oldenburg  
Germany

Phone: +49 441-680 06-11  
Fax: +49 441-680 06-15

E-mail: [sales@ise.de](mailto:sales@ise.de)  
Web: [www.ise.de](http://www.ise.de)