




SMART CONNECT KNX Panasonic

Product	Order number	VE	PP
 SMART CONNECT KNX Panasonic DRA, TP1	1-000C-000	1	1

Technical data

Rated voltage:	DC 24 V to 30 V
Power consumption:	2 W (24 V DC external supply)
Ambient temperature:	0 °C to +45 °C
KNX communication:	KNX/TP, S-Mode
KNX medium:	TP1-256
IP communication:	Ethernet 10/100 BaseT
Connections:	2x RJ45 (integrated switch) Connection and branching terminals for KNX and 24 V
Dimensions:	2 HP (DRA plus)

Information

Features:

- Separate control of up to four televisions
- Television on/off
- "Wake up" the TV device via Wake on LAN and then switch it on
- Volume control (switch sound on/off, increase or lower the volume or set the volume to the transferred value)
- Program control (change to the next or the previous program channel or change to a particular program channel)
- Transfer camera images, e.g. from an external camera
- Bookmark up to ten links
- Showing notices on the TV device: Use up to ten self-defined texts or dynamically display texts from other devices on the TV device, e.g. "Movement detected in garden" from an outside camera, display message as text
- Source selection (Flexibility of choice between the sources of the TV device, e.g. switch conveniently between HDMI input and receivers)
- Statusreport via KNX (current channel, current source, current volume, mute status, operating status, current errors)
- Simple integration in KNX (can be completely configured via ETS)
- Extensions via firmware updates

For supported Panasonic models and countries, see the Panasonic compatibility list on the product website under Technical data.

The product may slightly differ from the illustration.

12.01.2022

**ise Individuelle Software
und Elektronik GmbH**
Osterstraße 15
26122 Oldenburg
Germany

Phone: +49 441-680 06-11
Fax: +49 441-680 06-15
E-mail: sales@ise.de
Web: www.ise.de