

Unterstützte Ladepunkte

Supported charging points

| Hersteller Manufacturer | Modell/Typ Model/Type | Bemerkung Note | Modbus TCP | Modbus (RS485) | Phasenumschaltung möglich Phase switching possible |
|----------------------------|--------------------------|---|---------------|-------------------|---|
| ABB | EVLunic Pro S | ab v3.10.16 from v3.10.16 or higher | . | | Ja, extern Yes, external |
| | EVLunic Pro M | ab v1.11 from v1.11 or higher | . | | Ja, extern Yes, external |
| | Terra AC | ab v1.5.2 from v1.5.2 or higher Baudrate 57600 gefordert Baud rate 57600 required | | . | Nein No |
| ABL | eMH1 basic | Typ 1W2208 (22kW) | | . | Ja, extern Yes, external |
| | eMH1 | Typ 1W2201 (22kW) | | . | Ja, extern Yes, external |
| | | Typ 1W1121 (Ladesteckdose/charging socket) | | . | Ja, extern Yes, external |
| | | Typ 1W2221 (Ladesteckdose/charging socket) | | . | Ja, extern Yes, external |
| Alfen | Eve Single S-Line | Wichtig: Alfen Software Option „Load Balancing Active“ nötig Important: Requires Alfen software option „Load Balancing Active“ | . | | Nein No |
| | Eve Single Pro-Line | Wichtig: Alfen Software Option „Load Balancing Active“ nötig Important: Requires Alfen software option „Load Balancing Active“ | . | | Nein No |
| | Eve Double Pro-line | Wichtig: Alfen Software Option „Load Balancing Active“ nötig Important: Requires Alfen software option „Load Balancing Active“ | . | | Nein No |
| ebee | Berlin | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| ewe go (KEBA) | Wallbox Smart light | ab v3.10.16 from v3.10.16 or higher | . | | Ja, extern Yes, external |
| | Wallbox Smart | ab v1.11 from v1.11 or higher | . | | Ja, extern Yes, external |
| Heidelberg AmperfiED | Energy Control | Die Modbuslayout 1.08 wird benötigt. Ältere Geräte mit Typenschild Nr. 00.779.2885/02 und 00.779.2909 ohne Index sind nur nach einem Firmware-Up- date kompatibel. Modbus layout 1.08 is required. Older devices with type plate no. 00.779.2885/02 and 00.779.2909 without index are only compatible after a firmware update. | | . | Nein No |
| | connect.home | | . | | Nein No |
| KEBA | KeContact P30 c-series | ab v3.10.16 from v3.10.16 or higher | . | | Ja, extern Yes, external |
| | KeContact P30 x-series | ab v1.11 from v1.11 or higher | . | | Ja, extern Yes, external |

| Hersteller Manufacturer | Modell/Typ Model/Type | Bemerkung Note | Modbus TCP | Modbus (RS485) | Phasenumschaltung möglich Phase switching possible |
|----------------------------|--------------------------------------|---|---------------|-------------------|---|
| MENNEKES | 4You300 | | | . | Ja, intern Yes, internal |
| | AMTRON® Charge Control 11 | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMTRON® Charge Control 11 C2 | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMTRON® Professional | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMTRON® Professional PnC | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMTRON® Professional+ | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMTRON® Professional+ PnC | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMEDIO Professional | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMEDIO Professional+ | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMEDIO Professional PnC | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMEDIO Professional+ PnC | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMEDIO Professional with shutter | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMEDIO Professional PnC with shutter | ab v5.12 from v5.12 or higher | . | | Ja, extern Yes, external |
| | AMTRON® Premium C2 | | . | | Ja, extern Yes, external |
| | AMTRON® Premium E/R T2 | | . | | Ja, extern Yes, external |
| | AMTRON® Xtra C2 | | . | | Ja, extern Yes, external |
| | AMTRON® Xtra E/R T2 | | . | | Ja, extern Yes, external |
| | AMTRON® Compact 2.0s | | | . | Ja, intern Yes, internal |
| Schneider Electric | EVlink Wallbox G4 Smart | ab v3.4.0.3 from v3.4.0.3 or higher | . | | Ja, extern Yes, external |
| Schrack Technik | i-CHARGE CION Home | RFID Informationen nur ab Controller FW2.3 RFID information with controller FW 2.3 or higher | | . | Ja, extern Yes, external |
| | i-CHARGE CION Semipublic | RFID Informationen nur ab Controller FW2.3 RFID information with controller FW 2.3 or higher | | . | Ja, extern Yes, external |
| | i-CHARGE CION Pro | ab v5.20 from v5.20 or higher | . | | Ja, extern Yes, external |
| ELS Spelsberg | Wallbox Smart Pro | ab FW5.30 from FW5.30 or higher | . | | Ja, extern Yes, external |
| STÖHR | Design Tower | nur/only RTU | | . | |
| | Design Line | nur/only RTU | | . | |
| | Base Line | nur/only RTU | | . | |
| Walther Werke | smartEVO uno | ab FW5.21 from FW5.21 or higher | . | | Ja, extern Yes, external |
| | smartEVO uno + | ab FW5.21 from FW5.21 or higher | . | | Ja, extern Yes, external |
| | smartEVO uno connect | ab FW5.21 from FW5.21 or higher | . | | Ja, extern Yes, external |
| | smartEVO uno connect + | ab FW5.21 from FW5.21 or higher | . | | Ja, extern Yes, external |

Mit jedem Firmware-Update werden wir weitere Ladepunkte unterstützen! Ihr Ladepunkt ist noch nicht dabei? Schreiben Sie uns gerne eine E-Mail an support@ise.de
Further charging points will be supported with each firmware update! Your charging point is not yet included? Send us an E-Mail to support@ise.de